

Caricabatterie Manuali con Avviamento / Manual Battery Chargers and Starters

Tower 3500 - 5500

electromem
Battery Chargers & Starters

Caricabatterie con avviamento carrellati per la carica di tutti i tipi di accumulatori al piombo a 12 o 24 V e l'avviamento rapido di automobili, mezzi di trasporto, e mezzi da lavoro. Regolazione della corrente di carica e avviamento. Alimentazione 230 Volt monofase. Protezione contro sovraccarichi, cortocircuiti ed inversioni di polarità. Visualizzazione della corrente di carica e di avviamento.

Curva caratteristica di carica "W" a corrente decrescente, in accordo con la norma DIN 41774.

Wheel-carried battery chargers with starter for all kinds of lead storage batteries at 12 or 24 V and quick-starting of cars, means of transport and work. Charging and starting current regulation. Single phase 230 Volt power supply.

Overloads, short-circuits and polarity inversions safeguards. Charging and starting current visualization.

Characteristic "W" charge curve at decreasing current, according to DIN 41774 standard.



Made in Italy

DISPLAY DIGITALE PER LA
VISUALIZZAZIONE DELLA
CORRENTE / DIGITAL
DISPLAY SHOWING THE
CHARGE CURRENT



TOWER 5500



PROFESSIONAL

Model	Mains Voltage 50/60 Hz 1 Ph Volt	Power KWatt	Output Voltage Volt	Charge Current Eff. Amp	Charge Current Arith. Amp (d.c.)	Starting Current max. cc/1V(el) Amp	Current Regulation N°	Nominal Capacity to refer to Ah min max	Size mm	Weight kg	Cod. N
Tower 3500	230	1 - 5	12/24	45	30	300/200	6	30 - 350	330 x 245 x 730	14	06020
Tower 5500	230	1,5 - 10	12/24	75	50	450/300	6	30 - 550	330 x 280 x 800	18	06030