



Wifi Dongle for Solar I nverter

VT-660000 SKU: 11378





Plug and play No extra power supply is required



Waterproof design Resistant to bad weather

External design External indicator lights, ensuring collection status at a glance, easy to replace faulty equipment



Independent module Protecting internal parts of inverter







www.vtacexports.com ONE BRAND, ENDLESS SOLUTIONS.



GNSS

Antenna

SIM Card

Memory

Data Interface

Working Voltage

Working Power

Working Humidity

No. of Connections

User Configuration

Firmware Upgrade

Real-time Control

Power-off reminder

Data resuming

LSW-5 LSW-3 2.4G Wifi 2.4G Wifi **Remote Communication Interface** Internal Antenna **External Antenna** RS485/RS232/TTL DC 5-12V 1.5W 1.5W 2M Flash 8M Flash -40°C to +80°C Working Temperature <90% (No Condensation) One 9600bps(1200-115200bps Configurable) Serial Communication Rate Default: 5 mins (1-15 mins Configurable) Data Acquisition Interval BT/APP/Web APP/Web BT/Remote/Web Remote/Web $\sqrt{}$ $\sqrt{}$ $\sqrt{}$

SOLAR ENERGY





www.vtacexports.com ONE BRAND, ENDLESS SOLUTIONS.